Chemitec S.r.l. Via Molino della Splua, 28 - 10028 Trofarello (TO) Tel. 011 9451837 - Fax 011 9453322 email: info@chemitec.com



Technical note Rel. # 1 on 02/03/2020

ISODET

Hydroalcoholic decontaminant sanitizer with chlorhexidine digluconate

FEATURES

Hydro-alcoholic detergent with chlorhexidine suitable for cleaning and decontamination of all washable surfaces and equipment.

It is used in the food industry, in the community in general, in catering and healthcare companies.

The combined action of alcohol (75%) and chlorhexidine digluconate guarantee efficacy and excellent results in all conditions of use.

APPLICATIONS

Washing and sanitizing of washable surfaces in general, floors, tiles, walls, fixtures, furnishings, sanitary equipment in stainless steel or plastic.

ADVICE FOR USE

Spray as it is on the surface to be cleaned, rub and wait at least 30-40 seconds before removing the dirt with a paper or non-woven cloth.

PACKAGING

Box of 12x750 ml

STORAGE

The product retains its chemical, physical and technical characteristics unaltered if stored in a covered place and at temperatures between +5 and + 30 $^{\circ}$ C.

BIODEGRADABILITY

biodegradation:

The surfactants contained in this product comply with the biodegradability criteria established by the Regulation (EC) n.648 / 2004 relating to detergents.

CHEMICAL PHYSICAL FEATURES

Appearance: Clear pink liquid Odour: characteristic of alcohols pH: 8,5 - 9,56 at 100% Melting point/freezing point: -30° Initial boiling point and boiling range: 83° Flash point: 18° Flammability (solid, gas): Not applicable Upper/lower flammability or explosive limits: Not applicable Relative density: 0,835 - 0,840 Kg/dm³ a 20° C.

Disclaimer: The instructions and information in this document are the result of laboratory experiments and practical use and therefore accurate and relevant. Since the real conditions of use by users beyond any possibility of our control, they are supplied by us without any liability or warranty, either express or implied. For more information please contact our Technical Service.